



Feature	Specification
<b>Balloon Diameter</b>	1.00 mm - 4.00 mm
<b>Balloon Length</b>	10, 12, 15, 20, 30 mm
<b>Proximal Shaft (OD)</b>	1.9 Fr
<b>Distal Shaft (OD)</b>	2.36 Fr (Ø 1.00 - 1.75 mm) 2.55 Fr (Ø 2.00 - 3.00 mm) 2.70 Fr (Ø 3.50 - 4.00 mm)
<b>Working Length</b>	140 cm
<b>Guide Wire Compatibility</b>	0.014"
<b>Guiding Catheter Compatibility</b>	5 Fr Compatible/ 6 Fr Kissing Balloon Compatible
<b>Balloon Material</b>	Pebax
<b>Balloon Pleats</b>	Bi-fold (2 pleats) for Ø1.00 mm Tri-fold (3 pleats) for Ø1.25 mm - 4.00 mm
<b>Compliance</b>	Semi-Compliant
<b>Tip Entry Profile</b>	0.016"
<b>Tip Length</b>	1.50 mm (Ø 1.00 - 1.75 mm) 2.00 mm (Ø 2.00 - 3.00 mm) 2.50 mm (Ø 3.50 - 4.00 mm)
<b>Crossing Profile<sup>1</sup></b>	0.0186" (Ø 1.00 mm) 0.0190" (Ø 1.25 mm) 0.0193" (Ø 1.50 mm) 0.0196" (Ø 1.75 mm) 0.0199" (Ø 2.00 mm) 0.0202" (Ø 2.25 mm) 0.0205" (Ø 2.50 mm) 0.0208" (Ø 2.75 mm) 0.0210" (Ø 3.00 mm) 0.0217" (Ø 3.50 mm) 0.0223" (Ø 4.00 mm)
<b>Marker Bands</b>	2 Platinum Iridium Markers (Note: Only 1 marker for 1.00 mm - 175 mm balloons)
<b>Coating</b>	Hydrophilic outer surface coating from tip to guidewire exit port Hydrophobic coating inside guidewire lumena
<b>Nominal Pressure</b>	6 bar
<b>Rated Burst Pressure</b>	14 bar
<b>Average Burst Pressure</b>	20 bar
<b>Type</b>	Rapid Exchange (RX)
<b>Exit Marker</b>	Two markers located at 90 cm and 100 cm
<b>Information at hub and strain relief</b>	Configuration at strain relief (color: blue)

